eShelf® DPF13



13" Digital Photo Frame

(LUXX-DPF13-300)

Engaging shelf signage.



The 13" Digital Photo Frame is a sleek, high-definition display designed for 24/7 operation, making it perfect for continuous use in retail, hospitality, and other commercial settings. This stand-alone unit supports independent playback, allowing you to effortlessly display content without needing a network connection. Ideal for digital signage applications that require clear, eye-catching visuals in compact spaces.

Whether you're showcasing promotions, menus, or product information, this durable and energy-efficient display delivers sharp, vibrant content around the clock.

Vibrant



Our high-definition LCD display delivers crystal-clear visuals with vibrant colors and sharp details, ensuring your content stands out with stunning clarity.

Convenient



This stand-alone unit offers hassle-free operation, allowing you to play content directly without the need for a network or external connections.

Reliable



Supports 24/7 continuous operation, ensuring your content stays visible and engaging around the clock.

Let your message stand out

With a vibrant digital display.





Display	
Size	13"
Dimension	317 x 219 x 26mm
Active area	285(H) x 178(V) mm
Resolution	1280 x 800
Backlight	LED
Brightness (nits)	300cd/m ²
Lifespan	30000 hours
Viewing angle	Full Viewing Angle
Aspect Ratio	16:9

Black / White

Interface & Systems

Product color

No memory, need SD card/U disk Memory (Built-in memory on request)

Nor flash 16MB

Memory extension 32GB SD memory card Max

> 1*Mini USB (OTG), 1*SD Card, 1*USB Host 2.0,1*AV Output, 1*Power Input. Must

Interface match with our special adapter for power

supply

Built-in speakers 16Ω2w*2

Infrared remote control, 7 Key button Operation

English, Chinese (More options on request

- French, German, Spanish, Italian,

Portuguese, Dutch and Polish ect.)

Accessories

Language

Standard Remote Control, Stents, Instructions

Packing Info

G.W 1.2KG

Packing Dimension (10 Pcs/CTN) 670 x 345 x 335mm

G.W. (10 Pcs/CTN) 13KG

Power Input

DC 12V Voltage 1000mA Current

Environment

Temperature: 0°C ~ 50°C Working environment

Humidity: 10% ~ 85%

Atmospheric Pressure: 86KPa ~ 104KPa

Temperature: -20°C ~ 60°C

Humidity: 5% ~ 95% Storage environment

Atmospheric Pressure: 86kPa ~ 104kPa

Supported Media Formats

- Audio MP3、MP2、MP1、WMA、OGG、APE、FLAC、AC3、RA、 AAC...
- Video AVI、VOB、DAT、MP4、RM、RMVB、MKV、MOV、M4v 、MPG、FLV、PMP、3GP...
- · Picture JPG, JPEG

Warranty

1Y (more options on request) Year

Note: LCD screens, including Digital Photo Frame, may experience image retention or burn-in without effective content management.

What is Image Retention?

Image retention refers to any image that "sticks" on a screen, even when the content changes. It usually appears as a faint ghost that fades after a moment.

What is Image Burn-In?

Burn-in is a form of image retention that lasts much longer. It is a visible mark that remains, no matter what you are watching or doing.

Causes of Burn-In

- Videos that have a static logo, such as product logos, can leave a burn-in if displayed for a prolonged period
- · Pausing a video and leaving the Digital Photo Frame on for prolonged periods

Avoiding Burn-In

To prevent Digital Photo Frame burn-in,

- **AVOID** displaying static images or videos that have a static logo on Digital Photo Frame
- **ALWAYS** incorporate dynamic content to maintain Digital Photo Frame's quality over time.





13" Digital Photo Frame





Operation - 7 Buttons





Technical Data



