LUXX Light + Retail Technology

eShelf® ESP50A

35" Digital Stretch Screen

(LUXX-ESP50A-400)


Engaging shelf signage.



The 35" Digital Stretch Screen is a sleek, high-definition display designed for 24/7 operation, making it perfect for continuous use in retail, hospitality, and other commercial settings. This stand-alone unit supports independent playback, allowing you to effortlessly display content without needing a network connection. Ideal for digital signage applications that require clear, eye-catching visuals in compact spaces.

Whether you're showcasing promotions, menus, or product information, this durable and energy-efficient display delivers sharp, vibrant content around the clock.

Vibrant



Our high-definition LCD display delivers crystal-clear visuals with vibrant colors and sharp details, ensuring your content stands out with stunning clarity.

Convenient



This stand-alone unit offers hassle-free operation, allowing you to play content directly without the need for a network or external connections.

Reliable



Supports 24/7 continuous operation, ensuring your content stays visible and engaging around the clock.

Let your message stand out

With a vibrant digital display.



LCD Screen

Size 35"

Dimension 891.6 x 60.4 x 23.0mm

Active area 878.4(H) x 48.19(V) mm

Resolution $3840(V) \times 200(H)$

Backlight LED

Brightness (nits) 400cd/m²

Lifespan 30000 hours

Viewing angle $178^{\circ}(V) \times 178^{\circ}(H)$

Contrast 1000: 1

Frequency 60 Hz

Display color 1.07G

Response time 8 ms

Systems

CPU T972 Quad core ARM Cortex-A55 1.9GHz

RAM 2G (4G/8G optional)

ROM 16G EMMC (32G/64G EMMC optional)

Memory 128G TF, TF Card extension with the highest support

extension for 128GB

Networks

Built-in WIFI (default 2.4G single frequency,

configurable to 2.4G/5G dual frequency)

Bluetooth V4.2

1*micro USB (OTG), 1*USB-A, 1*TF card, 1*USB-C

Interface Power Input (DC12V). Must match with our special

adapter for power supply

OS Android 9.0

Packing Info

N.W ≤ 1.5KG

Packing Dimension (5 Pcs/CTN) 1120 x 320 x 140mm

G.W. 7.55KG

Accessories

Optional Power adapter, Mounting bracket, OTC

cable

Power

Power consumption ≤18W

Voltage DC 12V

Environment

Temperature: 0°C~50°C
Working environment Humidity: 10%~85%

Atmospheric Pressure: 86KPa~104KPa

Temperature: -20°C~60°C Humidity: 5%~95%

Storage environment Humidity: 5%~95%
Atmospheric Pressure: 86kPa~104kPa

Warranty

Year 1Y (more options on request)

Supported Media Formats

- Audio MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP formats
- Video Multi-format 1080P 60fps video decoding (H.265, H.264, VC-1, MPEG-1/2/4, VP8), 1080P video encoding, supports H.264, VP8
- Picture Supports browsing of various image formats such as JPG, BMP, PNG and supports rotation/slideshow/image enlargement functions

Note: LCD screens, including eShelf, may experience image retention or burn-in without effective content management.

What is Image Retention?

Image retention refers to any image that "sticks" on a screen, even when the content changes. It usually appears as a faint ghost that fades after a moment.

What is Image Burn-In?

Burn-in is a form of image retention that lasts much longer. It is a visible mark that remains, no matter what you are watching or doing.

Causes of Burn-In

- Videos that have a static logo, such as product logos, can leave a burn-in if displayed for a prolonged period
- Pausing a video and leaving the eShelf on for prolonged periods

Avoiding Burn-In

To prevent eShelf burn-in,

- AVOID displaying static images or videos that have a static logo on eShelf
- ALWAYS incorporate dynamic content to maintain eShelf's quality over time.







